



PRODUCT & TECHNICAL DATA

PRO UBER ALL EP 2

GENERAL PURPOSE LITHIUM GREASE

DESCRIPTION

Pro Uber All EP 2 is a multi-purpose grease incorporating an extreme pressure additive package, which possesses the additional advantage of improving corrosion protection and resistance to water. The NLGI consistency is a number 2. Pro Uber All Grease is based on high quality base oils blended with lithium hydroxystearate and calcium soap and possesses excellent mechanical stability as well as good load carrying, anti-corrosion and water-resisting properties. This grease is suitable for operations up to 160°C.

APPLICATIONS

Pro Uber All EP 2 Grease is most suitable for the lubrication of plain, needle, ball and roller bearings in the construction, machine tool, woodworking, textile and paper making industries, just to mention a few.

FEATURES AND ADVANTAGES

- Protects against rust and corrosion.
- Resistance to water washing.
- Good resistance to oxidation.
- Rationalized stock keeping.

PRO UBER ALL EP 2

PRODUCT AND TECHNICAL DATA

PHYSICAL CHARACTERISTICS

NLGI	2
4 Ball Weld Point (ASTM 2596), kfg	400
4 Ball Wear Scar (ASTM 2266), mm	0.57
Appearance, Visual	Light Brown, Brown
Drop Point, °C	273
Base Oil Viscosity @ 100 °cSt, mm ² /s	74
Recommended Temperature Range	-20° to 160°C

PRODUCT AND TECHNICAL DATA

Further information on all Pro Oil SA lubricants is available from any Pro Oil SA office or from:
www.prooil.co.za

These characteristics are typical of current production.
Whilst future production will conform to Pro Oil SA's specification, variations in these characteristics may occur.

Health and Safety

Guidance on Health and Safety are available on the appropriate Material Safety Data Sheet, which can be obtained from your Pro Oil SA representative.

The Pro Oil SA name and Pro Oil SA logo are trademarks of Pro Oil SA (PTY) LTD and are used under license.

Although all reasonable care has been taken to ensure that the information contained in this publication is accurate as at the time of printing, such information is nevertheless liable to variation in the event of changes occurring subsequent to the date of printing it: the blend formulation, methods of storage, or due to the improper handling or application of any of the products referred to, or in the requirements of any specification or approval relating to any of the products.

For more information, contact: Pro Oil SA (PTY) LTD
Unit 3, Shalem Park
60 Lauda Road
Killarney Gardens
Cape Town
South Africa
7411

Technical Advice Line: (+27) 21 556 6109
Customer Service: (+27) 21 556 6109