



## PRODUCT & TECHNICAL DATA



# PRO SYN TWO STROKE +

## SYNTHETIC TECHNOLOGY TWO STROKE PETROL ENGINE OIL

### DESCRIPTION

Pro Syn Two Stroke + is blended with a specified percentage of synthetic technology additives and base oils as well as a multifunctional additive package, containing anti-oxidants, anti-wear agents, anti-rust, detergents and dispersants. It is especially formulated to protect pre-ignition and spark plug fouling.

### APPLICATIONS

Pro Syn Two Stroke + is recommended for use in motorcycle engines, as well as two stroke chainsaws and brush cutters. It is a low smoke product with excellent rust protection during extended engine storage. Pro Syn Two Stroke + can be used for all oil injection systems that disperses very quickly when added to the fuel and enables the pre-mixtures to remain stable over long periods. Recommended ratio is 100:1.

PLEASE NOTE: This oil is not to be used in outboard engines. Please refer to Pro Super Outboard Oil.

### PERFORMANCE LEVELS

- JASO FD
- ISO L-EGD
- API-TC

### FEATURES AND ADVANTAGES

- High miscibility/fluidity.
- Easily identified with its blue colour.
- Promotes trouble free operations: spark plug fouling, pre-ignition.

## PRODUCT AND TECHNICAL DATA SHEET

# PRO SYN TWO STROKE +

## SYNTHETIC TECHNOLOGY TWO STROKE PETROL ENGINE OIL

### PHYSICAL CHARACTERISTICS

Colour	Blue
Viscosity @ 40 °cSt, mm <sup>2</sup> /s	82.28
Viscosity @ 100 °cSt, mm <sup>2</sup> /s	10.24
Viscosity Index	106
Pour Point, °C	-27
Flash Point, °C, Closed Cup	>200
Density @ 20°C, kg/l	0.868

### GENERAL ADVICE

Further information on all Pro Oil SA lubricants is available from any Pro Oil SA office or from:

[www.prooil.co.za](http://www.prooil.co.za)

These characteristics are typical of current production. Whilst future production will conform to Pro Oil SA's specification, variations in these characteristics may occur.

#### Health and Safety

Guidance on Health and Safety are available on the appropriate Material Safety Data Sheet, which can be obtained from your Pro Oil SA representative.

The Pro Oil SA name and Pro Oil SA logo are trademarks of Pro Oil SA (PTY) LTD and are used under license.

Although all reasonable care has been taken to ensure that the information contained in this publication is accurate as at the time of printing, such information is nevertheless liable to variation in the event of changes occurring subsequent to the date of printing it: the blend formulation, methods of storage, or due to the improper handling or application of any of the products referred to, or in the requirements of any specification or approval relating to any of the products.

#### For more information, contact:

Pro Oil SA (PTY) LTD  
104 Kyalami Drive  
Killarney Gardens  
Cape Town  
South Africa  
7411

#### Technical Advice Line:

(+27) 21 556 6109

#### Customer Service:

(+27) 21 556 6109