



PRODUCT & TECHNICAL DATA

PRO HD COMPLEX EP 2 (400)

HEAVY DUTY WHEEL BEARING AND GP GREASE

DESCRIPTION

Pro HD Complex EP 2 Grease is a multi-purpose lead free lithium complex grease, with excellent high temperature performance and long life capability. Good fretting corrosion performance, low water washout and good protection against bearing corrosion, combined with excellent mechanical stability and load-carrying capability makes it an ideal multi-purpose grease.

Pro HD Complex EP 2 consistently gives excellent high temperature performance and a wide operating temperature field from -20 °C to +150 °C.

APPLICATIONS

Pro HD Complex EP 2 is suitable for all grease applications. It is especially suitable for grease lubricated bearings at low and high speeds and is particularly recommended for wheel bearings, electrical motors and anti-friction bearings.

FEATURES AND ADVANTAGES

- Resistant to water wash out.
- Protects bearings against corrosion.
- Excellent lubrication properties.
- Long life.
- Economical.
- Good anti-wear properties.
- Excellent load carrying characteristics



PRODUCT & TECHNICAL DATA

PHYSICAL CHARACTERISTICS

NLGI	2
Appearance	Light Brown, Brown
Thickener	Lithium Complex
Drop Point, °C	>260
Timken OK load kg	>27
Worked Penetration	265-295
Usable Temperature Range, °C	-20 to +150
Base Oil Viscosity @ 40 °C, cSt	400
Viscosity Index	98

GENERAL ADVICE

Further information on all Pro Oil SA lubricants is available from any Pro Oil SA office or from:
www.prooil.co.za

These characteristics are typical of current production.
 Whilst future production will conform to Pro Oil SA's specification, variations in these characteristics may occur.

Health & Safety

Guidance on Health and Safety are available on the appropriate Material Safety Data Sheet, which can be obtained from your Pro Oil SA representative.

The Pro Oil SA name and Pro Oil SA logo are trademarks of Pro Oil SA and are used under license.

Although all reasonable care has been taken to ensure that the information contained in this publication is accurate as at the time of printing, such information is nevertheless liable to variation in the event of changes occurring subsequent to the date of printing it: the blend formulation, methods of storage, or due to the improper handling or application of any of the products referred to, or in the requirements of any specification or approval relating to any of the products.

For more information contact: Pro Oil SA
 Unit 1, Dale Park
 Killarney Gardens
 Cape Town
 South Africa
 7411

Technical Advice Line: (+27) 21 556 6109
 Customer Service: (+27) 21 556 6109

30/11/2011

